




MMB541 NEW

Micro ATX Motherboard with LGA1700 Socket 14th/13th/12th Gen Intel® Core™ Processor, Intel® H610, USB 3.2 Gen1x1, SATA 3.0, Dual GbE, 2.5GbE, VGA, DP and DVI-D



Features

- LGA1700 socket 14th/13th/12th gen Intel® Core™ i9/i7/i5/i3, Pentium® or Celeron® processor
- Dual 288-pin DDR4-3200 Long-DIMM, up to 64GB
- Supports triple-view display via DisplayPort, VGA, and DVI-D
- Supports M.2 Key M 2280/2242
- Supports USB 3.2 Gen1x1 and USB 2.0



▲ Side view

Specifications

Core System

CPU	LGA1700 socket 14th/13th/12th gen Intel® Core™ i9/i7/i5/i3, Pentium® or Celeron® processor (up to 125W)
System Memory	Dual 288-pin DDR4-3200 non-ECC Long-DIMM, up to 64GB
Chipset	Intel® H610
BIOS	AMI BIOS
SSD	M.2 Key M 2280/2242, supporting SATA SSD
Watchdog Timer	255 levels, 1 to 255 sec.
Expansion Interface	1 x PCIe Gen4 x16 slot 2 x PCIe Gen3 x2 from PCH (with x4 open-ended slots) 1 x 32-bit PCI slot, default clock is 33 MHz
Battery	Lithium 3V/220 mAH

Display

Chipset	Intel® UHD Graphics
Memory Size	Share system memory
Display Interface	1 x DisplayPort, up to 4096 x 2160@30Hz 1 x DVI-D, up to 1920 x 1200@60Hz 1 x VGA, up to 1920 x 1200@60Hz

I/O

SATA	3 x SATA-600 without RAID
Hardware Monitoring	Detect CPU/system temperature, voltage and supports smart fan control
Ethernet	1 x 10/100/1000/2500 Mbps with Intel® I226-V, supporting Wake-on-LAN and PXE Boot ROM 2 x 10/100/1000 Mbps with Intel® I210-AT, supporting Wake-on-LAN and PXE Boot ROM
Audio	HD Codec audio as Mic-in/Line-in/Line-out
USB	4 x USB 3.2 Gen1x1 (Type-A, rear I/O) 4 x USB 2.0 (Type-A, rear I/O) 1 x USB 2.0 (vertical Type-A, internal) 4 x USB 2.0 (header, internal)
Serial	4 x RS-232 (COM1/2/5/6, box header) 1 x RS-232/RS-485/RS-422 (COM3, box header) 1 x RS-232/RS-485 (COM4, box header)
TPM	Not included by default; supports Intel® PTT as default
SMBus	Yes
Digital I/O	8-channel programmable
Mechanical and Environmental	
Dimensions	244mm x 244mm
Board Thickness	1.6 mm
Operating Temperature	0°C to +60°C (+32°F to +140°F)
Humidity	10% to 95% relative humidity, non-condensing

Ordering Information

Standard

MMB541-H610-SP (P/N: E38W541101)	Micro ATX motherboard with LGA1700 socket 14th/13th/12th gen Intel® Core™ processor, Intel® H610, USB 3.2 Gen1x1, SATA 3.0, triple LAN including dual GbE and 2.5GbE, VGA, DisplayPort, and DVI-D; single packing
-------------------------------------	---

Optional

5938A808010E	2 x USB 2.0 cable with bracket, P=2.54 mm, L=190 mm
5938A808020E	2 x USB 2.0 cable with bracket, P=2.54 mm, L=400 mm
594G5208000E	SATA3 Cable 180D with lock & B.sleeve L50cm
59380402010E	1 x COM port cable with bracket, P=2.54 mm, L=300 mm
59380703000E	2 x COM port cable with bracket, P=2.54 mm, L=300 mm
713000000500	CPU heatsink for 1U chassis
711000002500	CPU cooler for 2U, 4U, and wall mount chassis

*Please refer to the user manual for the complete CPU list.